

KART NUMBER:

ENGINE SEAL NUMBER:

DRIVER NAME AND RACE CLASS (PLEASE PRINT):

DRIVER NAME:

RACE CLASS:

DIRECTIONS: PLEASE INDICATE COMPLIANCE FOR EACH ITEM BY CHECKING THE CORRESPONDING BOX. THIS FORM MUST BE SUBMITTED TO THE TSRS PRE-GRID STEWARD PRIOR TO ENTERING THE TRACK FOR YOUR <u>FIRST</u> COMPETITION SESSION (WHETHER THAT BE QUALIFYING, HEAT OR MAIN). FAILURE TO DO SO MAY RESULT IN A PENALTY ASSESSMENT, AS DETERMINED BY TSRS.

ITEMS THAT NEED TO BE SECURED BY NYLOCK, SAFETY WIRE, COTTER PINNED, OR SECURED BY CIRCLIP OR SNAP RING:

STEERING ASSEMBLY

- STEERING WHEEL TO HUB BOLTS
- STEERING HUB TO SHAFT BOLT
- STEERING SHAFT TO CHASSIS TIE
- ROD END BOLTS
- KINGPIN BOLTS
- SPINDLE NUT ATTACHING WHEEL

BRAKING SYSTEM

- PEDAL PIVOT TO CHASSIS
- ACTUATING ROD AND CABLE ENDS
- MASTER CYLINDER TO CHASSIS BOLTS
- CALIPER(S) TO CHASSIS BOLTS
- PAD RETAINING RODS
- BRAKE ROTOR TO HUB (METAL LOCK NUTS ONLY)
- CIK-SPECIFICATION BRAKE SAFETY CABLE WITH A MINIMUM DIAMETER OF 1.8MM

BODYWORK

01

- BODYWORK MOUNTED AS INTENDED BY MANUFACTURER
- MAXIMUM LENGTH AND WIDTH PER SKUSA RULEBOOK

FUEL (ALL CLASSES)

- SPEC FUEL: ASPEN SPORT 98 UNLEADED
 - IAME CLASSES ONLY:
- SPEC OIL: ELF HTX 909 SAE 50 MANDATORY RATIO: 1 GAL FUEL TO 6.76 OZ OIL

] 02[

EVENT RACE TIRES -- ENTER BAR CODE NUMBERS

GENERAL AND SAFETY REQUIREMENTS
WHICH MUST BE ADHERED TO:

- PUSH BACK BUMPERS ARE <u>NOT REQUIRED</u> FOR THIS EVENT
- CHASSIS TAG PROPERLY INSTALLED ON DRIVER'S RIGHT PER SKUSA RULE SECTIONS 252 AND 801
- ENGINE SEAL PROPERLY INSTALLED PER SKUSA RULE SECTIONS 253 AND 802/803
- CAMERA(S) MARKED WITH KART # AND MOUNTED PER SKUSA RULE SECTION 307.2
- BRAKE FUNCTIONALITY TEST -- SUFFICIENT FORCE APPLIED TO BRAKE PEDAL SHALL RESULT IN ALL APPLICABLE WHEELS BEING UNABLE TO TURN
- CHEST PROTECTORS FOR APPLICABLE DRIVERS PER SKUSA RULE 106.9
- SEAT MOUNTING TABS AND STRUTS IMPLEMENTED PER INTENT OF CHASSIS MANUFACTURER
- FUNCTIONAL FUEL AND WATER RECOVERY SYSTEM
- CORRECT KART NUMBER, COLOR AND BACKGROUND (4 LOCATIONS) AS APPROVED IN REGISTRATION
- **REAR PROTECTION MEETS CURRENT SKUSA RULES**
- WEIGHTS/BALLAST -- AND HARDWARE -- PAINTED WHITE • WEIGHT(S) UNDER 7 LBS. SECURED BY (1) 5/16" / 8MM BOLT
 - WEIGHT(S) 7+ LBS. SECURED BY TWO (2) 5/16" / 8MM BOLTS
 - DOUBLE NUTTED OR DRILLED WITH BOLT SAFETY-WIRED OR COTTER PINNED
- STARTER BATTERIES LABELED WITH KART # AND MOUNTED PER SKUSA RULE 402.3.1, INCLUDING 175-LB TIE WRAPS

04

- AUXILIARY THROTTLE CABLE RETURN SPRING (ALL CLASSES)
 - HELMET AND SUIT MEET LATEST SKUSA RULES. <u>MANDATORY</u>: ENTER THE HELMET RATING FROM THE INSIDE OF YOUR HELMET HERE:

SIGN	NED BY:	PLEASE PRINT THE NAME	OF THE SIGNER:
X			
L	COMPLETED, VERIFIED, AND WILL BE MAIN		ERTIFY THAT ALL ITEMS ON THIS FORM HAVE BEEN IE EVENT. ACCURACY OF THIS DOCUMENT IS 100% RESULT IN DISOLALIEICATION OR DENALTY

03